

GPR-1100

PPM Portable Oxygen Analyzer - GP or Certified for Hazardous Gas / Area use

Product Parent Code: GPR-1100 Rugged easy to use PPM General Purpose or Hazardous Area certified Portable Oxygen analyzer 4 measurement ranges: 0-10, 0-100, 0-1,000 PPM, 0-1% O2 plus 0-25% range for air calibration 0-1V DC signal output; internal data logging stainless steel wetted parts with 1/8" quick disconnect fittings rechargeable battery power with 9V charger; robust aluminum enclosure		
Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+...+{Feature X}		
Feature	Item	Description
Feature {A}	Base Model	
	GPR-1100	Portable Oxygen Analyzer (PPM)
Feature {B}	Configuration	
	B1	General Purpose
	B2	cMETus, ATEX, IECEX, UKEX
Feature {C}	Pump	
	C0	No sample system required
Feature {D}	Sensor	
	D1	GPR-12-333
	D2	XLT-12-333 (for CO2 & acidic background gases)
	D3	GPR-12-333-H (for H2 & He background gases)
Feature {M}	Certificates (Only add if required)	
	* M2	NIST Calibration Cert
Feature {X}	Options (only add if required)	
	* X1	Carrying Case
* On certain labor intensive services, no discount can be offered. These items are always offered at list price.		

Ordering Examples

GPR-1100 +B1+C0+D1+M1	Portable Oxygen Analyzer (PPM), General Purpose type, no pump, GPR-12-333 sensor, NIST Calibration certificate
------------------------------	---

Order Code	Description
Replacement Sensors	
GPR-12-333	PPM replacement sensor
XLT-12-333	PPM replacement sensor - CO2 & acidic background gases
GPR-12-333-H	PPM replacement sensor - H2 & He background gases
Accessories	
CONN-1034	Connector Output Mini Plug
FITN-1003	Quick Release Plug SS 1/8 FNPT
Spares	
A-4771	Battery w/o Pump
PWRS-1003-KIT	9V Power Charger - Universal AC Supply. Safe Area use only

GPR-1200

PPM Portable Oxygen Analyzer - GP or Certified for Hazardous Gas / Area use

Product Parent Code: GPR-1200 Premium PPM General Purpose or Hazardous Area certified Portable Oxygen analyzer 4 measurement ranges: 0-10, 0-100, 0-1,000 PPM, 0-1% O2 plus 0-25% range for air calibration 0-1V DC signal output; internal data logging provided with gas sample / sensor isolation valve, flow control needle valve and flow indicator; optional sample pump rechargeable battery power with 9V charger; robust aluminum enclosure		
Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+...+{Feature X}		
Feature	Item	Description
Feature {A}	Base Model	
	GPR-1200	Portable Oxygen Analyzer (PPM)
Feature {B}	Configuration	
	B1	General Purpose
	B2	cMETus, ATEX, IECEx, UKEX
Feature {C}	Hazardous Configuration	
	C0	No sample system required
	C2	Sample pump (suitable for B1 & B2)
	C3	Integral Pressure regulator
Feature {D}	Sensor	
	D1	GPR-12-333
	D2	XLT-12-333 (for CO2 & acidic background gases)
	D3	GPR-12-333-H (for H2 & He background gases)
Feature {M}	Certificates (Only add if required)	
	* M2	NIST Calibration Cert
Feature {X}	Options (only add if required)	
	* X1	Carrying Case
	* X2	Coalescing filter on inlet
	X3	6" H2S scrubber (for outlet)
	* X4	Panel mounted Coalescing Filter with 6" H2S scrubber
	* X5	Carrying Case (with H2S scrubber fitted)
* On certain labor intensive services, no discount can be offered. These items are always offered at list price.		

Ordering Examples

GPR-1200 +B2+C2+D1+M1+X1	Portable Oxygen Analyzer (PPM), ATEX, IS sample pump, GPR-12-333 sensor, NIST Calibration Cert, Carrying case
-------------------------------------	--

Order Code	Description
Replacement Sensors	
GPR-12-333	PPM replacement sensor
XLT-12-333	PPM replacement sensor - CO2 & acidic background gases
GPR-12-333-H	PPM replacement sensor - H2 & He background gases
Consumable Items	
CHEM-1008-2	H2S Scrubber Media 1 liter
FLTR-1037	Element for Coalescing Filter
Accessories	
CONN-1034	Connector Output Mini Plug
Spares	
A-2734-6	Spare H2S scrubber (outlet)
A-4442-1	Coalescing Filter Assembly
A-4770	Battery w/ Pump
A-4771	Battery w/o Pump
PWRS-1003-KIT	9V Power Charger - Universal AC Supply. Safe Area use only

GPR-2000

% Portable Oxygen Analyzer - GP or Certified for Hazardous Gas / Area use

Product Parent Code: GPR-2000 Rugged easy to use % General Purpose or Hazardous Area certified Portable Oxygen analyzer 4 measurement ranges: 0-1, 0-5, 0-10, 0-25% O2 0-1V DC signal output; internal data logging delrin sensor housing; stainless steel piping with 1/8" tube fittings rechargeable battery power with 9V charger; robust aluminum enclosure		
Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+...+{Feature X}		
Feature	Item	Description
Feature {A}	Base Model	
	GPR-2000	Portable Oxygen Analyzer %
Feature {B}	Configuration	
	B1	General Purpose
	B2	cMETus, ATEX, IECEx, UKEX
Feature {C}	Pump	
	C0	No sample system required
	C2	Sample pump (suitable for B1 & B2)
Feature {D}	Sensor	
	D1	GPR-11-60-4
	D2	XLT-11-24-4 (CO2 & acidic background gases)
Feature {M}	Certificates (Only add if required)	
	* M2	NIST Calibration Cert
Feature {X}	Options (only add if required)	
	* X1	Carrying Case
	* X2	Coalescing filter on inlet
	* X3	Panel with flowmeter
	* X4	Panel with coalescing filter and flowmeter
	* X5	Panel with coalescing filter, flowmeter and 6" H2S scrubber
	* X6	Carrying Case (with H2S scrubber fitted)
* On certain labor intensive services, no discount can be offered. These items are always offered at list price.		

Ordering Examples

GPR-2000 +B1+C0+D1+M1+X1	Portable Oxygen Analyzer, General Purpose type, no pump, GPR-11-32-4 sensor, NIST calibration cert, carrying case
---	--

Order Code	Description
Replacement Sensors	
GPR-11-60-4	% replacement sensor
XLT-11-24-4	% replacement sensor - CO2 & acidic background gases
Consumable Items	
CHEM-1008-2	H2S Scrubber Media 1 liter
FLTR-1037	Element for Coalescing Filter
Accessories	
CONN-1034	Connector Output Mini Plug
Spares	
A-2166	Pump Assembly (portable)
A-2734-6	Spare H2S scrubber (outlet)
A-4442-1	Coalescing Filter Assembly
A-4770	Battery w/ Pump
A-4771	Battery w/o Pump
A-4665	Pump Switch Assembly
A-5581	Sensor Cable Assembly (GPR-2000)
PWRS-1003-KIT	9V Power Charger - Universal AC Supply. Safe Area use only

GPR-3500 MOVR

Portable Oxygen Purity Analyzer

Product Parent Code: GPR-3500MOVR General Purpose Portable Oxygen Purity Analyzer 0-100% O2 measurement range 0-1V DC signal output; internal data logging stainless steel wetted parts, integral pressure regulator (3600 psig inlet), flow control needle valve, bypass valve, flow indicator and 1/8" inlet and 1/4" vent tube fittings rechargeable battery power with 9V charger; robust aluminum enclosure		
Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature X}		
Feature	Item	Description
Feature {A}	Base Model	
	GPR-3500MOVR	Portable Oxygen Analyzer (Purity)
Feature {B}	Sensor	
	B1	GPR-11-120-OP
Feature {M}	Certificates (Only add if required)	
	* M2	NIST Calibration Cert
Feature {X}	Options (only add if required)	
	* X1	Carrying Case
* On certain labor intensive services, no discount can be offered. These items are always offered at list price.		

Ordering Examples

GPR-3500 MOVR+B1+M1	Portable Oxygen Analyzer, GPR-11-120-OP sensor, NIST calibration certificate
----------------------------	---

Order Code	Description
Replacement Sensors	
GPR-11-120-OP	Purity replacement sensor
Accessories	
CONN-1034	Connector Output Mini Plug
Spares	
PWRS-1003-KIT	9V Power Charger - Universal AC Supply. Safe Area use only

GPR-7100

Portable H2S Analyzer (PPM) - Certified for Hazardous Gas / Area use

Product Parent Code: GPR-7100		
Rugged easy to use PPM Hazardous Area certified Portable H2S Analyzer		
measurement ranges: 0-20, 0-50, 0-100 PPM H2S or 0-500, 0-1000, 0-2000 PPM H2S		
0-1V DC signal output; internal data logging		
Supplied with coalescing filter; dual flowmeters for sample and air dilution drawn by integral pump; stainless steel wetted parts and 1/8" tube fittings		
rechargeable battery power with 9V charger; robust aluminum enclosure		
Product Ordering Code {Feature A}+{Feature B}+{Feature C}+{Feature D}+...+{Feature X}		
Feature	Item	Description
Feature {A}	Base Model	
	GPR-7100	Portable H2S analyzer (PPM)
Feature {C}	Sampling System	
	C0	No sample system required
	C1	6" H2S scrubber (for outlet)
Feature {D}	Sensor	
	D1	OSV-72-7HH: (0-20, 0-50, 0-100PPM)
	D2	OSV-72-7H: (0-500, 0-1000, 0-2000PPM)
Feature {X}	Optiond (Only add if required)	
	* X1	Carrying Case
* On certain labor intensive services, no discount can be offered. These items are always offered at list price.		

Ordering Examples

GPR-7100+C1+D2+X1	Portable Intrinsically safe H2S analyzer (PPM), 6" H2S scrubber (for outlet) sampling, OSV-72-7H: (0-500, 0-1000, 0-2000PPM) sensor, Carrying Case
--------------------------	---

Order Code	Description
Replacement Sensors	
OSV-72-7HH	PPM H2S replacement sensor - (0-20, 0-50, 0-100PPM)
OSV-72-7H	PPM H2S replacement sensor - (0-500, 0-1000, 0-2000PPM)
Consumable Items	
CHEM-1008-2	H2S Scrubber Media 1 liter
FLTR-1037	Element for Coalescing Filter
Accessories	
CONN-1034	Connector Output Mini Plug
Spares	
A-4442-1	Coalescing Filter Assembly
A-2166	Pump Assembly (portable)
A-2734-6	Spare H2S scrubber (outlet)
A-4770	Battery w/ Pump
PWRS-1003-KIT	9V Power Charger - Universal AC Supply. Safe Area use only

Please note: Analytical Industries Inc. adopts a continuous development program which sometimes necessitates specification changes without notice. Please contact us for the latest version. Issue No: GPR-1000/1200/1100/2000/3500/7100 Order Codes_V5